


SAGA

Fingerprint Safe

F-X20FO

SAGA safes have simple instructions and are easy to operate
Full with originality, innovation, stylish and convenience!



Product Features

Optical Fingerprint Sensor:	solid surface plated membrane 300,000 pixels colourful CMOS
Resolution:	500 dpi
Resist And Assault Ability:	4H pencil assault 1000 times in succession within the range of 20cm
Matching Time:	≤ 1second
Matching Mode:	1:N
FRR (False Rejection Rate):	< 1%
FAR (False Acceptance Rate):	< 0.0001%
Fingerprint Reader:	360°
Fingerprint Capacity:	30
Light Interference:	out light or sunshine directly acceptance nanometer plated membrane protected surface , increasing wear resisting degree
Optical Glass:	
Static consumption:	<10uA
Dynamic consumption:	≤120mA
Communication Protocol:	TTL or Serial (RS232)
Operating Voltage:	DC 4.5-7V(4 xAA size Alkaline Batteries)
Using Environment Temperature:	5 °C ~ 50 °C
Operating Humidity:	45%RH ~ 80% RH

Specification

Model No.:	F-X20FO
External:	(H)200×(W)420×(D)370 mm
Internal:	(H)178×(W)416×(D)314 mm
Door opening:	(H)160×(W)328 mm
Packing dimension:	(H)248×(W)454×(D)439 mm
Net Weight:	12.5 kg
Gross Weight:	13.5 kg
Shelf(PC):	without, Double locking bolt
Colors available:	Black
20'FLC (PCS):	585 units / cartons